



ALIMENTATORI/DRIVER NON DIMMERABILI NOT DIMMABLE POWER SUPPLIES/DRIVERS




DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE
DRIVER INPUT 230Vac OUTPUT CONSTANT CURRENT

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE079	100-240Vac	500mA	12W	IP20	115x34x19mm	1 (Ulisse, Teseco)
TE049	220-240Vac	500mA	25W	IP20	Ø72x24mm	1-2 (Ulisse, Teseco)
TE052	220-240Vac	700mA	8W	IP20	58x35x21mm	1 (Ulisse, Teseco, Glacier RTL)
TE072	90-264Vac	700mA	20W	IP67	118x35x38mm	1-2 (Ulisse, Teseco, Glacier RTL) 1 (Glacier RZL)
TE054	220-240Vac	700mA	25W	IP20	Ø72x24mm	1-2 (Ulisse, Teseco, Glacier RTL) 1 (Glacier RZL)
TE061	220-240Vac	700mA	32W	IP20	116x46x34mm	1-4 (Ulisse, Teseco, Glacier RTL) 1-2 (Glacier RZL)
TE073	90-264Vac	700mA	35W	IP67	148x40x30mm	1-4 (Ulisse, Teseco, Glacier RTL) 1-2 (Glacier RZL)



DRIVER INGRESSO 230Vca USCITA 24Vdc
DRIVER INPUT 230Vac OUTPUT 24Vdc

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE036	90-264Vac	24Vdc	20W	IP67	118x35x29mm
TE037	90-264Vac	24Vdc	35W	IP67	148x40x30mm
TE038	90-264Vac	24Vdc	60W	IP67	163x46x32mm
TE039	90-264Vac	24Vdc	100W	IP67	190x52x37mm
TE066	90-305Vac	24Vdc	150W	IP67	228x68x39mm
TE069	90-305Vac	24Vdc	240W	IP67	251x68x39mm
TE070	90-305Vac	24Vdc	320W	IP67	252x90x44mm



ALIMENTATORE INGRESSO 230Vca USCITA 12V PER ALOGENE
POWER SUPPLY INPUT 230Vac OUTPUT 12V FOR HALOGEN BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE053	220-240Vac	12V	35-105W	IP20	128x38x31mm

Compatibile con lampada della gamma PARATHOM by Osram (GU4, GU5.3, G53)
Compatible with PARATHOM bulbs by Osram (GU4, GU5.3, G53 socket)

Dimmerabile a taglio di fase in discesa.
Dimmable by trailing-edge phase cut.




ALIMENTATORE INGRESSO 230Vca PER LAMPADA A SCARICA
POWER SUPPLY INPUT 230Vac FOR HID BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE001	198-264Vac	250Vac	70W	IP20	155x83x32mm

DIMMER E ALIMENTATORI/DRIVER DIMMERABILI DIMMERS AND DIMMABLE POWER SUPPLIES/DRIVERS


QUBA FLUO 50 QUBA FLUO 60



ALIMENTATORE DIMMERABILE. Ingressi controllo: DALI, TOUCH DIM
DIMMABLE POWER SUPPLY. Control inputs: DALI, TOUCH DIM

CODE	INPUT	ARTICLE	HOUSING	IP	TECHNICAL DATA	DIM. (LxWxH)
TE026	220-240Vac	Quba fluo 50	Inside product	IP20	1x38W 2G11	360x30x21mm
TE023	220-240Vac	Quba fluo 60	Inside product	IP20	1x55W 2G11	360x30x21mm


STRIPE GO T5 E T5 SEAMLESS



ALIMENTATORE DIMMERABILE. Ingressi controllo: DALI, TOUCH DIM
DIMMABLE POWER SUPPLY. Control inputs: DALI, TOUCH DIM

CODE	INPUT	ARTICLE	HOUSING	IP	TECHNICAL DATA	DIM. (LxWxH)
TE027	220-240Vac	Stripe	Inside product	IP20	1x14/24W T5	360x30x21mm
TE029	220-240Vac	Stripe	Inside product	IP40	1x21/39W T5	360x30x21mm
TE023	220-240Vac	Stripe	Inside product	IP20	1x28/54W T5	360x30x21mm
TE031	220-240Vac	Stripe	Inside product	IP20	1x35/49W T5	360x30x21mm
TE033	220-240Vac	Stripe	Inside product	IP20	1x80W T5	360x30x21mm


STRIPE GO LED



DRIVER INGRESSO 230Vca USCITA 24V PWM. Ingressi controllo: DALI, TOUCH DIM
DRIVER INPUT 230Vac OUTPUT 24V PWM. Control inputs: DALI, TOUCH DIM

CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
TE020	198-264Vac	24V PWM	Remote mounting	75W	IP20	220x47x44mm


STRIPE GO LED



DIMMER MONOCANALE. Ingressi controllo: pulsante, 1-10V
DIMMER ONE CHANNEL. Control inputs: push button, 1-10V


CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
TE040	24Vdc	24V PWM	Remote mounting or DIN bar	192W	IP20	90x17x59mm

COSTANT CURRENT LED WALL / CEILING



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante e IGBT-TRIAC
DRIVER INPUT 230Vac OUTPUT CONSTANT CURRENT. Control Input: push button and IGBT-TRIAC

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE088	198-264Vac	350mA	17W	IP20	166x46x34mm	
	198-264Vac	500mA	24W	IP20	166x46x34mm	1-2 (Ulisse, Teseco)
	198-264Vac	700mA	32W	IP20	166x46x34mm	1-4 (Ulisse, Teseco, Glacier RTL), 1-2 (Glacier RZL)



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante, DALI e 1-10V
DRIVER INPUT 230Vac OUTPUT CONSTANT CURRENT. Control Input: push button, DALI and 1-10V

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE089	99-264Vac	350mA	40W	IP20	124x79x22mm	
	99-264Vac	500mA	50W	IP20	124x79x22mm	1-4 (Ulisse, Teseco)
	99-264Vac	700mA	50W	IP20	124x79x22mm	1-8 (Ulisse, Teseco, Glacier RTL), 1-3 (Glacier RZL)