



DIAPSON TRACK COINLIGHT

design Luce Lab


Proiettore a LED da binario, orientabile in modo indipendente, disponibile in acciaio lucido e cromo o nella finitura bianco opaco. Compresa la lampada a LED CoinLight (by Osram), alimentatore incluso. Diapson Track Coinlight viene fornito completo di adattatore Eurostandard. La lampada è disponibile nelle tre versioni: da 18W (CRI 92), da 22,5W e da 33,8W, con due temperature colore (3000K e 4000K) e due tipologie di apertura fascio (24° e 40°). Ideale per una varietà di soluzioni illuminotecniche per un'illuminazione concentrata e d'accento grazie ai fasci di luce direzionali e ai diversi gradi di apertura disponibili.

LED track projector, independently adjustable, available in polished stainless steel and chrome or white painted finish.

Including Coinlight LED lamp (by OSRAM), power supply included. Diapson Track Coinlight is supplied with Eurostandard adapter. The light fixture is available in three versions: 18W (CRI 92), 22,5W and 33,8W with two colour temperatures (3000K and 4000K) and with two opening angles (24° and 40°). Suitable for a variety of concentrated and accent lighting solutions thanks to the directional light beams and the different opening angles available.

LED
INSIDE

DIAPSON TRACK COINLIGHT



1 x 18W (22W*) 230Vac COINLIGHT (inclusa/included)

CRI 92

IP20 Classe 1 **A** **CE**

Alimentatore 700mA incluso / 700mA power supply included

CODE	FINISHINGS	LIGHT BEAM	COLOUR TEMPERATURE
TS702 LC	01 04	M Lens 24°	K3 3000K 1130lm (5040 cd)
TS702 LC	01 04	W Lens 40°	K3 3000K 1130lm (2335 cd)
TS702 LC	01 04	M Lens 24°	K4 4000K 1200lm (5325 cd)
TS702 LC	01 04	W Lens 40°	K4 4000K 1200lm (2465 cd)

1 x 22,5W (26W*) 230Vac COINLIGHT (inclusa/included)

IP20 Classe 1 **A** **CE**

Alimentatore 700mA incluso / 700mA power supply included

CODE	FINISHINGS	LIGHT BEAM	COLOUR TEMPERATURE
TS702 LA	01 04	M Lens 24°	K3 3000K 1740lm (7705 cd)
TS702 LA	01 04	W Lens 40°	K3 3000K 1740lm (3570 cd)
TS702 LA	01 04	M Lens 24°	K4 4000K 1850lm (8155 cd)
TS702 LA	01 04	W Lens 40°	K4 4000K 1850lm (3780 cd)


1 x 33,8W (39W*) 230Vac COINLIGHT (inclusa/included)

IP20 Classe 1 **A** **CE**

Alimentatore 1050mA incluso / 1050mA power supply included

CODE	FINISHINGS	LIGHT BEAM	COLOUR TEMPERATURE
TS702 LB	01 04	M Lens 24°	K3 3000K 2550lm (11230 cd)
TS702 LB	01 04	W Lens 40°	K3 3000K 2550lm (5200 cd)
TS702 LB	01 04	M Lens 24°	K4 4000K 2700lm (11885 cd)
TS702 LB	01 04	W Lens 40°	K4 4000K 2700lm (5505 cd)

PHOTOMETRICS



ACCESSORIES

* Potenza totale assorbita dal corpo illuminante / Total absorbed power by the lighting fixture