

PARETE
WALL

STRIPE SYSTEM PARETE LED

design Luce Lab

Sistema a parete costituito da un profilo in alluminio al metro elettrificato con una o due strip led (19,2 W/m, 1520 lm/m) IP20, passo 2,5cm, e un diffusore in PMMA satinato.

Lo starting kit, il diffusore, la lunghezza del profilo e il numero di moduli e/o accessori vanno specificati nell'ordine.

Disponibile in alluminio anodizzato nei colori alluminio naturale satinato, titanio spazzolato e cromo brillantato e nelle verniciature bianco lucido e nero opaco. Disponibile con 3 temperature colore del bianco: K3, K4, K6 (caldo 3200K, neutro 4300K, freddo 6000K).

Wall mounting system made up of an aluminium profile per meter electrified with one or two IP20 LED strips with high luminous flux 1520 lm/m (19,2 W/m), 2,5 cm pitch, and a satin PMMA diffuser. The starting kit, the diffuser, the length of the profile and the number of elements and/or accessories must be specified in the order.


Available in the following anodized aluminium colours natural satin aluminium, shiny chrome and brushed titanium and in the following painted versions: shiny white and matt black.

Available in three white colour temperatures K3, K4, K6 (warm 3200K, neutral 4300K, cold 6000K).

LED
INSIDE


STRIPE PARETE LED

MODULO AL METRO
ELEMENT PER METER



TS537 LZ

TS533 LA



TS538 LZ

TS534 LA

1 STRIP LED P.2,5 cm 19,2W/m 24Vdc

IP43 IP40 ∇ \diamond **A+** **CE**

Alimentatore non incluso / Power supply not included


CODE	FINISHINGS	COLOUR TEMPERATURE	LUMINOUS FLUX
TS537 LZ	03 07 31 32 33	K3 3200K	1504lm/m
TS537 LZ	03 07 31 32 33	K4 4300K	1520lm/m
TS537 LZ	03 07 31 32 33	K6 6000K	1600lm/m
TS533 LA	03 07 31 32 33	STARTING KIT 1 STRIP LED	

2 STRIP LED P.2,5 cm 19,2W/m 24Vdc


IP43 IP40 ∇ \diamond **A+** **CE**

Alimentatore non incluso / Power supply not included


CODE	FINISHINGS	COLOUR TEMPERATURE	LUMINOUS FLUX
TS538 LZ	03 07 31 32 33	K3 3200K	3008lm/m
TS538 LZ	03 07 31 32 33	K4 4300K	3040lm/m
TS538 LZ	03 07 31 32 33	K6 6000K	3200lm/m
TS534 LA	03 07 31 32 33	STARTING KIT 2 STRIP LED	




PHOTOMETRICS




COMPONENTS



Diffusore
Diffuser
TS506 XX
al metro / per meter



Staffa di giunzione
per parete
Metal junction bar
for wall element
TS513



Alimentatore
Power Supply
pag. 108



Kit dimmerabile
Dimmable kit
pag. 108