



## ALIMENTATORI/DRIVER NON DIMMERABILI NOT DIMMABLE POWER SUPPLIES/DRIVERS




DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE  
DRIVER INPUT 230Vac OUTPUT CONSTANT CURRENT

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
<b>TE079</b>	100-240Vac	500mA	12W	IP20	115x34x19mm	1 (Ulisse, Teseo)
<b>TE049</b>	220-240Vac	500mA	25W	IP20	Ø72x24mm	1-2 (Ulisse, Teseo)
<b>TE052</b>	220-240Vac	700mA	8W	IP20	58x35x21mm	1 (Ulisse, Teseo, Glacier R1L)
<b>TE072</b>	90-264Vac	700mA	20W	IP67	118x35x36mm	1-2 (Ulisse, Teseo, Glacier R1L) 1 (Glacier R2L)
<b>TE054</b>	220-240Vac	700mA	25W	IP20	Ø72x24mm	1-2 (Ulisse, Teseo, Glacier R1L) 1 (Glacier R2L)
<b>TE061</b>	220-240Vac	700mA	32W	IP20	116x46x34mm	1-4 (Ulisse, Teseo, Glacier R1L) 1-2 (Glacier R2L)
<b>TE073</b>	90-264Vac	700mA	35W	IP67	148x40x30mm	1-4 (Ulisse, Teseo, Glacier R1L) 1-2 (Glacier R2L)



DRIVER INGRESSO 230Vca USCITA 24Vdc  
DRIVER INPUT 230Vac OUTPUT 24Vdc

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
<b>TE036</b>	90-264Vac	24Vdc	20W	IP67	118x35x26mm
<b>TE037</b>	90-264Vac	24Vdc	35W	IP67	148x40x30mm
<b>TE038</b>	90-264Vac	24Vdc	60W	IP67	163x46x32mm
<b>TE039</b>	90-264Vac	24Vdc	100W	IP67	190x52x37mm
<b>TE066</b>	90-305Vac	24Vdc	150W	IP67	228x68x39mm
<b>TE069</b>	90-305Vac	24Vdc	240W	IP67	251x68x39mm
<b>TE070</b>	90-305Vac	24Vdc	320W	IP67	252x90x44mm




ALIMENTATORE INGRESSO 230Vca USCITA 12V PER ALOGENE  
POWER SUPPLY INPUT 230Vac OUTPUT 12V FOR HALOGEN BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
<b>TE053</b>	220-240Vac	12V	35-105W	IP20	128x38x31mm

Compatibile con lampada della gamma PARATHOM by Osram (GU4, GU5.3, G53)  
Compatible with PARATHOM bulbs by Osram (GU4, GU5.3, G53 socket)

Dimmerabile a taglio di fase in discesa.  
Dimmable by trailing-edge phase cut.




ALIMENTATORE INGRESSO 230Vca PER LAMPADE A SCARICA  
POWER SUPPLY INPUT 230Vac FOR HID BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
<b>TE001</b>	198-264Vac	250Vac	70W	IP20	155x83x32mm

## DIMMER E ALIMENTATORI/DRIVER DIMMERABILI DIMMERS AND DIMMABLE POWER SUPPLIES/DRIVERS


### QUBA FLUO 50 QUBA FLUO 60



ALIMENTATORE DIMMERABILE. Ingressi controllo: DALI, TOUCH DIM  
DIMMABLE POWER SUPPLY. Control inputs: DALI, TOUCH DIM

CODE	INPUT	ARTICLE	HOUSING	IP	TECHINAL DATA	DIM. (LxWxH)
<b>TE026</b>	220-240Vac	Quba fluo 50	Inside product	IP20	1x36W 2G11	360x30x21mm
<b>TE023</b>	220-240Vac	Quba fluo 60	Inside product	IP20	1x55W 2G11	360x30x21mm


### STRIPE GO T5 E T5 SEAMLESS



ALIMENTATORE DIMMERABILE. Ingressi controllo: DALI, TOUCH DIM  
DIMMABLE POWER SUPPLY. Control inputs: DALI, TOUCH DIM

CODE	INPUT	ARTICLE	HOUSING	IP	TECHINAL DATA	DIM. (LxWxH)
<b>TE027</b>	220-240Vac	Stripe	Inside product	IP20	1x14/24W T5	360x30x21mm
<b>TE029</b>	220-240Vac	Stripe	Inside product	IP40	1x21/39W T5	360x30x21mm
<b>TE023</b>	220-240Vac	Stripe	Inside product	IP20	1x28/54W T5	360x30x21mm
<b>TE031</b>	220-240Vac	Stripe	Inside product	IP20	1x35/49W T5	360x30x21mm
<b>TE033</b>	220-240Vac	Stripe	Inside product	IP20	1x80W T5	360x30x21mm


### STRIPE GO LED



DRIVER INGRESSO 230Vca USCITA 24V PWM. Ingressi controllo: DALI, TOUCH DIM  
DRIVER INPUT 230Vac OUTPUT 24V PWM. Control inputs: DALI, TOUCH DIM

CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
<b>TE020</b>	198-254Vac	24V PWM	Remote mounting	75W	IP20	220x47x44mm


### STRIPE GO LED



DIMMER MONOCANALE. Ingressi controllo: pulsante, 1-10V  
DIMER ONE CHANNEL. Control inputs: push button, 1-10V


CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
<b>TE040</b>	24Vdc	24V PWM	Remote mounting or DIN bar	192W	IP20	90x17x58mm

### COSTANT CURRENT LED WALL / CEILING



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante e IGBT-TRIAC  
DRIVER INPUT 230Vac OUTPUT COSTANT CURRENT. Control Input: push button and IGBT-TRIAC

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
<b>TE088</b>	198-264Vac	350mA	17W	IP20	166x46x34mm	
	198-264Vac	500mA	24W	IP20	166x46x34mm	1-2 (Ulisse, Teseo)
	198-264Vac	700mA	32W	IP20	166x46x34mm	1-4 (Ulisse, Teseo, Glacier R1L), 1-2 (Glacier R2L)



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante, DALI e 1-10V  
DRIVER INPUT 230Vac OUTPUT COSTANT CURRENT. Control Input: push button, DALI and 1-10V

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
<b>TE089</b>	99-264Vac	350mA	40W	IP20	124x79x22mm	
	99-264Vac	500mA	50W	IP20	124x79x22mm	1-4 (Ulisse, Teseo)
	99-264Vac	700mA	50W	IP20	124x79x22mm	1-6 (Ulisse, Teseo, Glacier R1L), 1-3 (Glacier R2L)