



INCASSI SENZA BORDI
RECESSED LIGHT FRAMELESS

STRIPE SYSTEM FRAMELESS T5

design Giampiero Derai

Sistema ad incasso frameless costituito da moduli elettrificati, profili in alluminio senza bordo che alloggiavano lampade T5 normali e diffusore in PMMA o schermo darklight.

Disponibile nella anodizzazione alluminio naturale spazzolato o verniciato bianco lucido.

Le lampade T5 sono disponibili nelle due versioni:

HE per massimizzare l'efficienza luminosa e per avere una luminanza costante anche con moduli di differenti potenze; HO per ottenere il maggior flusso luminoso. Si consiglia l'utilizzo di lampade HO nelle installazioni con moduli della stessa potenza.

Recessed frameless system made up of electrified modules, aluminium profiles without edges designed for housing normal T5 lamps and PMMA diffusers or darklight screen.

Available in the brushed natural anodized aluminium and shiny white finishings.

The T5 lamps are available in two versions:

HE to maximize the luminous efficiency and get a constant luminance even by different elements with several lengths and powers; HO to obtain the maximum luminous flux. The use of HO lamps is advised for installation of several elements with the same power.

STRIPE 60 FRAMELESS

IP43 IP23 IP40 IP20 Classe 1

1 x 14W G5 230Vac T5-HE

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FA	07 31	1350lm (1,7 cd/cm ²)

TS514 FA 07 31 1350lm (1,7 cd/cm²)

1 x 24W G5 230Vac T5-HO

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FB	07 31	2000lm (2,5 cd/cm ²)

TS514 FB 07 31 2000lm (2,5 cd/cm²)

STRIPE 90 FRAMELESS

1 x 21W G5 230Vac T5-HE

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FC	07 31	2100lm (1,7 cd/cm ²)

TS514 FC 07 31 2100lm (1,7 cd/cm²)

1 x 39W G5 230Vac T5-HO

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FD	07 31	3500lm (2,8 cd/cm ²)

TS514 FD 07 31 3500lm (2,8 cd/cm²)

STRIPE 120 FRAMELESS

1 x 28W G5 230Vac T5-HE

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FE	07 31	2900lm (1,7 cd/cm ²)

TS514 FE 07 31 2900lm (1,7 cd/cm²)

1 x 54W G5 230Vac T5-HO

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FF	07 31	5000lm (2,9 cd/cm ²)

TS514 FF 07 31 5000lm (2,9 cd/cm²)

STRIPE 150 FRAMELESS

1 x 35W G5 230Vac T5-HE

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FG	07 31	3650lm (1,7 cd/cm ²)

TS514 FG 07 31 3650lm (1,7 cd/cm²)

1 x 49W G5 230Vac T5-HO

CODE	FINISHINGS	LUMINOUS FLUX
TS514 FH	07 31	4900lm (2,3 cd/cm ²)



TS514 FH 07 31 4900lm (2,3 cd/cm²)

1 x 80W G5 230Vac T5-HO


CODE	FINISHINGS	LUMINOUS FLUX
TS514 FI	07 31	7000lm (3,2 cd/cm ²)

TS514 FI 07 31 7000lm (3,2 cd/cm²)

PHOTOMETRICS



FORO / HOLE:
L_{TOT} (mm) x 47
L_{TOT} (mm) = Σ L1 + 9 mm



MODULE 60 L1= 585 mm
MODULE 90 L1= 885 mm
MODULE 120 L1= 1185 mm
MODULE 150 L1= 1485 mm